


ARMY RESEARCH LABORATORY



# Laser Ignition of Propellants in Closed Chambers

R. A. Beyer  
L.-M. Chang  
B. E. Forch

ARL-TR-1055

April 1996

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

19960418 049

DTIC QUALITY INSPECTED 1

## **NOTICES**

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE April 1996		3. REPORT TYPE AND DATES COVERED Final, Oct 90 - Sep 91
4. TITLE AND SUBTITLE  Laser Ignition of Propellants in Closed Chambers			5. FUNDING NUMBERS  PR: 1L162618AH80	
6. AUTHOR(S) R. A. Beyer, L. -M. Chang, and B. E. Forch				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  U.S. Army Research Laboratory ATTN: AMSRL-WT-PC Aberdeen Proving Ground, MD 21005-5066			8. PERFORMING ORGANIZATION REPORT NUMBER  ARL-TR-1055	
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT  Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  Preliminary experiments have been performed in the application of laser ignition to solid and liquid propellants in closed chambers. The effect of confinement on ignitability and the ignition of a range of energetic materials are demonstrated.				
14. SUBJECT TERMS  black powder, propellant, flamespread, laser ignition			15. NUMBER OF PAGES 21	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

INTENTIONALLY LEFT BLANK.

## TABLE OF CONTENTS

		<u>Page</u>
	LIST OF FIGURES .....	v
1.	INTRODUCTION .....	1
2.	EXPERIMENTAL .....	2
3.	OBSERVATIONS: SINGLE CHAMBER .....	3
3.1	Black Powder (BP) .....	3
3.2	M30 Propellant .....	4
3.3	M43 Propellant .....	4
3.4	LP1846 .....	5
4.	OBSERVATIONS: DOUBLE CHAMBER .....	6
4.1	Solid Propellants .....	6
4.2	LP .....	7
5.	OBSERVATIONS: GUN SIMULATOR .....	8
6.	SUMMARY AND CONCLUSIONS .....	10
7.	FUTURE WORK .....	10
8.	REFERENCES .....	11
	DISTRIBUTION LIST .....	13

INTENTIONALLY LEFT BLANK.

## LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. Schematic diagram of laser ignition chamber .....	2
2. BP pressure response to laser ignition in small cell .....	3
3. M30 laser ignition .....	4
4. M43 ignition on third pulse .....	5
5. Laser ignition of LP1846 .....	5
6. M30 laser ignition in dual chamber fixture .....	6
7. Ignition of previously ignited and quenched M43 in dual chamber .....	7
8. LP1846 ignition with 6.5J of laser energy in the dual chamber vessel .....	8
9. LP1846 ignition with 8.5J of laser energy .....	8
10. Ignition of LP1846 with vented second chamber .....	9
11. Schematic diagram of 25-mm gun chamber simulator .....	9
12. Pressure trace from ignition of JA2 with BP assisted laser ignition in 25-mm simulator .....	10

INTENTIONALLY LEFT BLANK.



## 1. INTRODUCTION

The application of laser ignition to gun propulsion systems is being pursued for many potential advantages. These advantages have been discussed in detail elsewhere (Barrows et al. 1991). Laser ignition may hold solutions to the difficulty of achieving effective ignition of a two-piece cartridge for the Advanced Tank Cannon System (ATACS) or the Modular Artillery Charge System (MACS) for artillery. Laser ignition has also received increasing attention because of its potential to achieve multi-point ignition, simultaneously or in a programmed time sequence. Based on numerical analyses (Williams and Chang 1991), there are indications that ignition in a programmed sequence along the charge length may achieve the goal of high muzzle velocity without the appearance of pressure waves. In addition, the use of low vulnerability propellants (LOVA) has become a major trend in gun design. However, the difficult-to-ignite characteristics of these propellants make it difficult to obtain effective ignition with a conventional igniter system. Furthermore, the performance of advanced charges is sometimes less reproducible and is more sensitive to temperature change than conventional ammunition. All of these problems demand a strong consideration of alternate ignition systems, such as laser ignition.

Although the concept of using laser pulses to ignite propellant is not new, the technology must be advanced before the concept becomes practical. The major difficulty is to ignite a propelling charge with an ignition delay acceptable to gun users. To meet this requirement, various laser beam parameters can be explored, such as power, energy, flux, and wavelength. While direct ignition of the propellants is desirable, it is difficult to achieve and remains a long-term goal of the program. In indirect ignition, the laser ignites an energetic material of higher ignitability that is embedded in the propellant bed. The combustion products then ignite the surrounding propellant.

The ready ignition of several propellants in the open air has been earlier demonstrated in our lab and elsewhere. In the present work, studies have been begun to study ignition in confined vessels, which are a step closer to ignition in a gun chamber. This report discusses primarily the ignition of small samples of solid and liquid propellant (LP) that are confined by a chamber with limited ullage. The ignition characteristics are observed and guidelines are set for future work.

## 2. EXPERIMENTAL

The chamber used in most of these studies is shown in cross section in Figure 1. It was machined out of 316 stainless steel and has a chamber capacity of  $0.1 \text{ cm}^3$ . While it was originally designed with a sapphire window, the use of the mylar as a combination window and blowout disk has proven to be advantageous for bench top survey studies. The transmission of the mylar is much less than typical windows or fiber optics, but that creates no difficulty for these studies. The chamber is held together by six bolts. The back wall is formed by the pressure gauge, as shown. No protective grease was used on the gauge because of the very limited volume. There were also concerns that the grease would introduce significant nonreproducible effects on the volume and heat transfer to the walls. Thus all pressure traces have the characteristic negative shift due to heating of the pressure transducer; this shift is only cosmetic for these studies.




Figure 1. Schematic diagram of laser ignition chamber.

The laser used in these studies was a neodymium glass laser operating at  $1.054\text{-}\mu\text{m}$  wavelength with pulse length variable from  $100 \mu\text{s}$  to  $10 \text{ ms}$  and variable energy. For these studies, the light was focused to a  $0.125\text{-in}$ -diameter spot with a  $2\text{-in}$  focal length lens. Except as noted, the mylar was  $0.020 \text{ in}$  thick (four layers of  $0.005 \text{ in}$  each). For some of the studies, a second expansion chamber was created by adding a spacer after the diaphragm with a second diaphragm. In most cases, the volume of this second chamber was  $0.05 \text{ cm}^3$ . This arrangement allowed the study of how completely the propellant was ignited, and whether sudden, but incomplete, depressurization would extinguish it. The results obtained from this configuration will also be important in the study of laser ignition where the irradiated material could be

placed in a confined volume to enhance ignition; after ignition, the confinement would rupture and the following processes take place in a depressurized environment.

### 3. OBSERVATIONS: SINGLE CHAMBER

In most of the observations described here, a graphite coating was required on the propellant surface in order to have sufficient energy absorbed to ignite the sample. Whether the problem is reflection or transmission of the light has not yet been determined definitely, except in obvious cases such as M9 where it is possible to burn objects behind the propellant sample with the transmitted light.

3.1 Black Powder (BP). One material not needing a coating to enhance absorption was BP. This material was tested as a bench mark because of its ease of ignition and rapid flamespread. A typical pressure trace is shown in Figure 2. For this record, as much sample was put into the volume as possible without grains damaging the diaphragm, which resulted in an estimated 60–70% loading density. A 10-ms laser pulse was used. The time zero in the figure is the start of the laser pulse. Approximately 1.5 J of energy was incident on the sample surface before ignition, which occurred at about 4.5 ms; this short time is adequate for most gun system minimum requirements. Note that the pressure gauge does not go negative before the event due to the opacity of the sample. As expected in the event, the ignition was clean and unambiguous. BP is unique among the materials tested in that the confinement and pressurization appear to have little effect on the ignition and flamespread rates.




Figure 2. BP pressure response to laser ignition in small cell.

3.2 M30 Propellant. Figure 3 shows the typical behavior of a slice of M30 propellant grain when tested in the same manner. Note that the pressure gauge is heated by the laser prior to the ignition. Since this sample required a graphite coating for prompt ignition, the light probably was going either around the propellant or through the perforations in the grain. Approximately 5 J of light energy was incident on the propellant surface before ignition took place. As with the BP, this value was well above any threshold and merely a convenient value to ensure ignition. A comparison of Figure 3 with Figure 2 shows that the pressure rise was noticeably slower for the M30 grain, indicating a slower ignition and flamespread process.




Figure 3. M30 laser ignition.

3.3 M43 Propellant. Several LOVA propellants were studied briefly. The response of one of these, M43, is shown in Figure 4. Approximately 8.5 J of laser energy were incident on the solid surface during 10 ms. As can be seen in the plot, the laser raised the pressure sufficiently that full ignition of the propellant took place shortly thereafter. The pressure rise was much slower in comparison with BP and M30 propellant in the previous Figures. This result was expected because of the difficulty of igniting the LOVA propellants.

In many of these experiments, careful measurements were made of the mass lost by the propellant sample during the event by weighing the samples before and after the event. In this case, the original sample was 90.0 mg before irradiation and 86.6 mg after the event shown. The mass lost by a similar piece of material under the same laser conditions, but without confinement and ignition, showed a mass loss of approximately 0.1 mg, which is at our level of measurement uncertainty. The amount of mass lost




Figure 4. M43 ignition on third pulse.

when an M43 propellant sample was ignited for these brief times varied from 2 to 9 mg and appeared to be independent of the original mass.

3.4 LP1846. Although the liquid propellants are also quite transparent at  $1.054\ \mu\text{m}$ , most experiments were done without adding graphite. It also ignited vigorously and promptly with the laser source. As can be seen in Figure 5, ignition delay was about 5.5 ms for this typical example. The LP is most obviously different from the solids in that it blew itself out of the chamber almost completely. In the single diaphragm experiments, it behaved much like the M43 in the sense of needing good confinement and pressurization during the laser pulse in order to achieve ignition.




Figure 5. Laser ignition of LP1846.

#### 4. OBSERVATIONS: DOUBLE CHAMBER

As mentioned, it was decided to provide the propellants a little more burning space, in part to establish that they were really vigorously burning and to increase the measured mass loss. Three examples of typical behavior are presented here.

4.1 Solid Propellants. The energy to the surface for the M30 event shown in Figure 6 was less than 3 J before the apparent ignition time. As can be seen, the second diaphragm broke at a lower pressure than the first. The pressure behavior before the burst of the first diaphragm is quite similar to that recorded in the single chamber ignition, such as shown in Figure 3. In the case of Figure 6, the sample lost 12.1 mg, or 9.5% of the total mass. A similar record for an M43 sample is shown in Figure 7. Note that the ignition in this case is more prompt and unambiguous than in the sample shown for the single chamber ignition of the same material; this behavior is due to the use of a previously burned and extinguished propellant sample. The pressure record again shows good sustained ignition. The sample from this and similar tests show the smooth, glassy surface and enlarged perforations that are indicative of flamespread over the entire surface.




Figure 6. M30 laser ignition in dual chamber fixture.




Figure 7. Ignition of previously ignited and quenched M43 in dual chamber.

4.2 LP. The behavior of LP1846 in the double chamber studies was significantly different from the solid propellants. As can be seen in Figure 8, the second peak is very sharply rising and goes higher in pressure before the diaphragm can burst and relieve the pressure. In addition, inspection of the diaphragms after the event show similar behavior for the first diaphragm for solids and liquids but differences in the second. In the case of solid propellants and the first diaphragm of the LPs, the two burst patterns are typical of a stretch-and-break event. The second LP disks show a larger, smoother hole that probably has experienced a much greater flow of high-temperature materials (gas or liquid). The main difference here is probably due to the in-depth heating, reaction, and ignition of the LPs (i.e., when they ignite, the whole volume is involved rather than just the surface). The pressure traces are shown in Figures 8 and 9 for two levels of irradiation. The observed behavior with similar shapes but shorter times with greater energy is classical laser ignition behavior.

Some brief effort was made to develop a second chamber with a small vent that might simulate an igniter component for LPs. The goal is to keep the pressure elevated to continue combustion while venting hot gases and reactive chemical species to use for ignition. In Figure 10, an example is shown for LP1846 where the venting of pressure sustained the event for about 10 ms beyond what would have occurred with closed chamber. Similar tests were done with solid propellants. In some of these cases, significantly longer burn times were achieved.




Figure 8. LP1846 ignition with 6.5J of laser energy in the dual chamber vessel.




Figure 9. LP1846 ignition with 8.5J of laser energy.

## 5. OBSERVATIONS: GUN SIMULATOR

Preliminary studies have been made of laser ignition in a 25-mm gun chamber simulator designed to scale the behavior of larger guns (see Figure 11). While both BP-assisted ignition and direct laser ignition were explored briefly, the efficient coupling of the laser energy into the propellant has not been adequately demonstrated in these brief studies. As expected, ignition using BP was readily achieved. An example






Figure 10. Ignition of LP1846 with vented second chamber.

of an event using a small amount of BP attached to the surface of a JA2 grain to assist ignition of the grain is shown in Figure 12. In this test, the grain was placed near the window at the breech end of the simulator with the rest of the chamber filled with inert grains. In the figure, the first and second pressure rises are due to the ignition of the BP and the JA2 grain, respectively. Inspection of the grain after the event, which was terminated by the diaphragm burst and grain extinguishment, again showed good flamespread to the extent that the perforations were enlarged and joined at some parts of the grain. While direct ignition of JA2 was achieved in this simulator, it has not been done with reasonable delay or good reproducibility. Obvious difficulties to be addressed for direct ignition include heat loss to the window if the grain is tightly packed against the window and efficiently coupling of the energy into the propellant.




Figure 11. Schematic diagram of 25-mm gun chamber simulator.

## 6. SUMMARY AND CONCLUSIONS

A variety of propellants have been shown to be readily ignitable by laser light at a wavelength that is producible in compact, efficient package size. Ignition delay times vary substantially around the typical values shown here; the major uncontrolled variable is presently thought to be the coupling of the energy into the propellant.

## 7. FUTURE WORK

As discussed in the preceding descriptions, future work will include efforts to couple light more efficiently into the propellants, wavelength studies, application of fiber optics for multi-point ignition of a propelling charge, and extensive studies with gun simulators.




Figure 12. Pressure trace from ignition of JA2 with BP assisted laser ignition in 25-mm simulator.

## 8. REFERENCES

Barrows, A. W., B. E. Forch, R. A. Beyer, A. Cohen, and J. E. Newberry. "Laser Ignition in guns, Howitzers, and Tanks: The Light Program." 28th JANNAF Combustion Subcommittee Meeting, CPIA Pub. 573, vol. I, p. 441, 1991.

Williams, A. W., and L.-M. Chang. "Simulator Studies of a Two-Piece Cartridge Ignition System." 28th JANNAF Combustion Subcommittee Meeting, CPIA Pub. 573, vol. III, p. 205, 1991.

INTENTIONALLY LEFT BLANK.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	DEFENSE TECHNICAL INFO CTR ATTN DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218
1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TA 2800 POWDER MILL RD ADELPHI MD 20783-1145
3	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TL 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TP 2800 POWDER MILL RD ADELPHI MD 20783-1145
	<u>ABERDEEN PROVING GROUND</u>
5	DIR USARL ATTN AMSRL OP AP L (305)

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	HQDA ATTN SARD TT DR F MILTON PENTAGON WASHINGTON DC 20310-0103
1	HQDA ATTN SARD TT MR J APPEL PENTAGON WASHINGTON DC 20310-0103
1	HQDA OASA RDA ATTN DR C H CHURCH PENTAGON ROOM 3E486 WASHINGTON DC 20310-0103
4	COMMANDER US ARMY RESEARCH OFFICE ATTN R GHIRARDELLI D MANN R SINGLETON R SHAW P O BOX 12211 RSCH TRNGLE PK NC 27709-2211
1	DIRECTOR ARMY RESEARCH OFFICE ATTN AMXRO RT IP LIB SERVICES P O BOX 12211 RSCH TRNGLE PK NC 27709-2211
2	COMMANDER US ARMY ARDEC ATTN SMCAR AEE B D S DOWNS PCTNY ARSNL NJ 07806-5000
2	COMMANDER US ARMY ARDEC ATTN SMCAR AEE J A LANNON PCTNY ARSNL NJ 07806-5000
1	COMMANDER US ARMY ARDEC ATTN SMCAR AEE BR L HARRIS PCTNY ARSNL NJ 07806-5000
2	COMMANDER US ARMY MISSILE COMMAND ATTN AMSMI RD PR E A R MAYKUT AMSMI RD PR P R BETTS REDSTONE ARSENAL AL 35809

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	OFFICE OF NAVAL RESEARCH DEPARTMENT OF THE NAVY ATTN R S MILLER CODE 432 800 N QUINCY STREET ARLINGTON VA 22217
1	COMMANDER NAVAL AIR SYSTEMS COMMAND ATTN J RAMNARACE AIR 54111C WASHINGTON DC 20360
2	COMMANDER NAVAL SURFACE WARFARE CENTER ATTN R BERNECKER R 13 G B WILMOT R 16 SILVER SPRING MD 20903-5000
5	COMMANDER NAVAL RESEARCH LABORATORY ATTN M C LIN J MCDONALD E ORAN J SHNUR R J DOYLE CODE 6110 WASHINGTON DC 20375
2	COMMANDER NAVAL WEAPONS CENTER ATTN T BOGGS CODE 388 T PARR CODE 3895 CHINA LAKE CA 93555-6001
1	SUPERINTENDENT NAVAL POSTGRADUATE SCHOOL DEPT OF AERONAUTICS ATTN D W NETZER MONTEREY CA 93940
3	AL LSCF ATTN R CORLEY R GEISLER J LEVINE EDWARDS AFB CA 93523-5000
1	AFOSR ATTN J M TISHKOFF BOLLING AIR FORCE BASE WASHINGTON DC 20332

NO. OF  
COPIES ORGANIZATION

1 OSD SDIO IST  
ATTN L CAVENY  
PENTAGON  
WASHINGTON DC 20301-7100

1 COMMANDANT  
USAFAS  
ATTN ATSF TSM CN  
FORT SILL OK 73503-5600

1 UNIV OF DAYTON RSCH INSTITUTE  
ATTN D CAMPBELL  
AL PAP  
EDWARDS AFB CA 93523

1 NASA  
LANGLEY RESEARCH CENTER  
ATTN G B NORTHAM MS 168  
LANGLEY STATION  
HAMPTON VA 23365

4 NATIONAL BUREAU OF STANDARDS  
US DEPARTMENT OF COMMERCE  
ATTN J HASTIE  
M JACOX  
T KASHIWAGI  
H SEMERJIAN  
WASHINGTON DC 20234

2 DIRECTOR  
LAWRENCE LIVERMORE NATIONAL LAB  
ATTN C WESTBROOK  
W TAO MS L 282  
P O BOX 808  
LIVERMORE CA 94550

1 DIRECTOR  
LOS ALAMOS NATIONAL LAB  
ATTN B NICHOLS T7 MS B284  
P O BOX 1663  
LOS ALAMOS NM 87545

2 PRINCETON COMBUSTION  
RESEARCH LABORATORIES INC  
ATTN N A MESSINA  
M SUMMERFIELD  
PRINCETON CORPORATE PLAZA  
BLDG IV SUITE 119  
11 DEERPARK DRIVE  
MONMOUTH JUNCTION NJ 08852

NO. OF  
COPIES ORGANIZATION

3 DIRECTOR  
SANDIA NATIONAL LABORATORIES  
DIVISION 8354  
ATTN S JOHNSTON  
P MATTERN  
D STEPHENSON  
LIVERMORE CA 94550

1 BRIGHAM YOUNG UNIVERSITY  
DEPT OF CHEMICAL ENGINEERING  
ATTN M W BECKSTEAD  
PROVO UT 84058

1 CALIFORNIA INSTITUTE OF TECH  
JET PROPULSION LABORATORY  
ATTN L STRAND MS 125 224  
4800 OAK GROVE DRIVE  
PASADENA CA 91109

1 CALIFORNIA INSTITUTE OF TECHNOLOGY  
ATTN F E C CULICK MC 301 46  
204 KARMAN LAB  
PASADENA CA 91125

1 UNIVERSITY OF CALIFORNIA  
LOS ALAMOS SCIENTIFIC LAB  
P O BOX 1663 MAIL STOP B216  
LOS ALAMOS NM 87545

1 UNIVERSITY OF CALIFORNIA BERKELEY  
CHEMISTRY DEPARMENT  
ATTN C BRADLEY MOORE  
211 LEWIS HALL  
BERKELEY CA 94720

1 UNIVERSITY OF CALIFORNIA SAN DIEGO  
ATTN F A WILLIAMS  
AMES B010  
LA JOLLA CA 92093

2 UNIV OF CALIFORNIA SANTA BARBARA  
QUANTUM INSTITUTE  
ATTN K SCHOFIELD  
M STEINBERG  
SANTA BARBARA CA 93106

1 UNIV OF COLORADO AT BOULDER  
ENGINEERING CENTER  
ATTN J DAILY  
CAMPUS BOX 427  
BOULDER CO 80309-0427

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
3	UNIV OF SOUTHERN CALIFORNIA DEPT OF CHEMISTRY ATTN R BEAUDET S BENSON C WITTIG LOS ANGELES CA 90007
1	CORNELL UNIVERSITY DEPARTMENT OF CHEMISTRY ATTN T A COOL BAKER LABORATORY ITHACA NY 14853
1	UNIVERSITY OF DELAWARE CHEMISTRY DEPARTMENT ATTN T BRILL NEWARK DE 19711
1	UNIVERSITY OF FLORIDA DEPT OF CHEMISTRY ATTN J WINEFORDNER GAINESVILLE FL 32611
3	GEORGIA INSTITUTE OF TECHNOLOGY SCHOOL OF AEROSPACE ENGINEERING ATTN E PRICE W C STRAHLE B T ZINN ATLANTA GA 30332
1	UNIVERSITY OF ILLINOIS DEPT OF MECH ENG ATTN H KRIER 144MEB 1206 W GREEN ST URBANA IL 61801
1	THE JOHNS HOPKINS UNIV CPIA ATTN T W CHRISTIAN 10630 LITTLE PATUXENT PKWY SUITE 202 COLUMBIA MD 21044-3200
1	UNIVERSITY OF MICHIGAN GAS DYNAMICS LAB ATTN G M FAETH AEROSPACE ENGINEERING BLDG ANN ARBOR MI 48109-2140
1	UNIVERSITY OF MINNESOTA DEPT OF MECHANICAL ENGINEERING ATTN E FLETCHER MINNEAPOLIS MN 55455

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
4	PENNSYLVANIA STATE UNIVERSITY DEPT OF MECHANICAL ENGINEERING ATTN K KUO M MICCI S THYNELL V YANG UNIVERSITY PARK PA 16802
2	PRINCETON UNIVERSITY FORRESTAL CAMPUS LIBRARY ATTN K BREZINSKY I GLASSMAN P O BOX 710 PRINCETON NJ 08540
1	PURDUE UNIVERSITY SCHL OF AERONAUTICS & ASTRONAUTICS ATTN J R OSBORN GRISSOM HALL WEST LAFAYETTE IN 47906
1	PURDUE UNIVERSITY DEPARTMENT OF CHEMISTRY ATTN E GRANT WEST LAFAYETTE IN 47906
2	PURDUE UNIVERSITY SCHL OF MECHANICAL ENGNRNG ATTN N M LAURENDEAU S N B MURTHY TSPC CHAFFEE HALL WEST LAFAYETTE IN 47906
1	RENSSELAER POLYTECHNIC INST DEPT OF CHEMICAL ENGINEERING ATTN A FONTIJN TROY NY 12181
1	STANFORD UNIVERSITY DEPT OF MECHANICAL ENGINEERING ATTN R HANSON STANFORD CA 94305
1	UNIVERSITY OF TEXAS DEPT OF CHEMISTRY ATTN W GARDINER AUSTIN TX 78712
1	VA POLYTECH INST AND STATE UNIV ATTN J A SCHETZ BLACKSBURG VA 24061



<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	APPLIED COMBUSTION TECHNOLOGY INC ATTN A M VARNEY P O BOX 607885 ORLANDO FL 32860
2	APPLIED MECHANICS REVIEWS ASME ATTN R E WHITE & A B WENZEL 345 E 47TH STREET NEW YORK NY 10017
1	TEXTRON DEFENSE SYSTEMS ATTN A PATRICK 2385 REVERE BEACH PARKWAY EVERETT MA 02149-5900
1	BATTELLE TWSTIAC 505 KING AVENUE COLUMBUS OH 43201-2693
1	COHEN PROFESSIONAL SERVICES ATTN N S COHEN 141 CHANNING STREET REDLANDS CA 92373
1	EXXON RESEARCH & ENG CO ATTN A DEAN ROUTE 22E ANNANDALE NJ 08801
1	GENERAL APPLIED SCIENCE LABS INC 77 RAYNOR AVENUE RONKONKAMA NY 11779-6649
1	GENERAL ELECTRIC ORDNANCE SYSTEMS ATTN J MANDZY 100 PLASTICS AVENUE PITTSFIELD MA 01203
1	GENERAL MOTORS RSCH LABS PHYSICAL CHEMISTRY DEPARTMENT ATTN T SLOANE WARREN MI 48090-9055
2	HERCULES INC ATTN W B WALKUP E A YOUNT P O BOX 210 ROCKET CENTER WV 26726

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	HERCULES INC ATTN R V CARTWRIGHT 100 HOWARD BLVD KENVIL NJ 07847
1	ALLIANT TECHSYSTEMS INC MARINE SYSTEMS GROUP ATTN D E BRODEN MS MN50 2000 600 2ND STREET NE HOPKINS MN 55343
1	ALLIANT TECHSYSTEMS INC ATTN R E TOMPKINS MN 11 2720 600 SECOND ST NORTH HOPKINS MN 55343
1	IBM CORPORATION RESEARCH DIVISION ATTN A C TAM 5600 COTTLE ROAD SAN JOSE CA 95193
1	IIT RESEARCH INSTITUTE ATTN R F REMALY 10 WEST 35TH STREET CHICAGO IL 60616
1	LOCKHEED MISSILES & SPACE CO ATTN GEORGE LO 3251 HANOVER STREET DEPT 52 35 B204 2 PALO ALTO CA 94304
1	OLIN ORDNANCE ATTN V MCDONALD LIBRARY P O BOX 222 ST MARKS FL 32355-0222
1	PAUL GOUGH ASSOCIATES INC ATTN P S GOUGH 1048 SOUTH STREET PORTSMOUTH NH 03801-5423
1	HUGHES AIRCRAFT COMPANY ATTN T E WARD PO BOX 11337 TUCSON AZ 85734-1337

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	SCIENCE APPLICATIONS INC ATTN R B EDELMAN 23146 CUMORAH CREST WOODLAND HILLS CA 91364
3	SRI INTERNATIONAL ATTN G SMITH D CROSLEY D GOLDEN 333 RAVENSWOOD AVENUE MENLO PARK CA 94025
1	STEVENS INSTITUTE OF TECH DAVIDSON LABORATORY ATTN R MCALEVY III HOBOKEN NJ 07030
1	SVERDRUP TECHNOLOGY INC LERC GROUP ATTN R J LOCKE MS SVR 2 2001 AEROSPACE PARKWAY BROOK PARK OH 44142
1	SVERDRUP TECHNOLOGY INC ATTN J DEUR 2001 AEROSPACE PARKWAY BROOK PARK OH 44142
3	THIOKOL CORPORATION ELKTON DIVISION ATTN R BIDDLE R WILLER TECH LIB P O BOX 241 ELKTON MD 21921
3	THIOKOL CORPORATION WASATCH DIVISION ATTN S J BENNETT P O BOX 524 BRIGHAM CITY UT 84302
1	UNITED TECHNOLOGIES RSCH CENTER ATTN A C ECKBRETH EAST HARTFORD CT 06108
1	UNITED TECHNOLOGIES CORP CHEMICAL SYSTEMS DIVISION ATTN R R MILLER P O BOX 49028 SAN JOSE CA 95161-9028

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	UNIVERSAL PROPULSION COMPANY ATTN H J MCSPADDEN 25401 NORTH CENTRAL AVENUE PHOENIX AZ 85027-7837
1	VERITAY TECHNOLOGY INC ATTN E B FISHER 4845 MILLERSPORT HIGHWAY EAST AMHERST NY 14051-0305
1	FREEDMAN ASSOCIATES ATTN E FREEDMAN 2411 DIANA ROAD BALTIMORE MD 21209-1525
3	ALLIANT TECHSYSTEMS ATTN C CANDLAND L OSGOOD R BECKER 600 SECOND ST NE HOPKINS MN 55343
1	DIRECTOR US ARMY BENET LABS ATTN AMSTA AR CCB T SAM SOPOK WATERVLIET NY 12189

NO. OF  
COPIES ORGANIZATION

ABERDEEN PROVING GROUND

42 DIR USARL  
ATTN: AMSRL-WT-P, A HORST  
AMSRL-WT-PA,  
A BIRK  
T P COFFEE  
J DESPIRITO  
J D KNAPTON  
C LEVERITT  
G P WREN  
AMSRL-WT-PC,  
R A FIFER  
G F ADAMS  
W R ANDERSON  
R A BEYER  
S W BUNTE  
C F CHABALOWSKI  
K P MCNEILL-BOONSTOPPEL  
A COHEN  
R CUMPTON  
R DANIEL  
D DEVYNCK  
N F FELL  
B E FORCH  
J M HEIMERL  
A J KOTLAR  
M R MANAA  
W F MCBRATNEY  
K L MCNESBY  
S V MEDLIN  
M S MILLER  
A W MIZIOLEK  
S H MODIANO  
J B MORRIS  
J E NEWBERRY  
S A NEWTON  
R A PESCE-RODRIGUEZ  
B M RICE  
R C SAUSA  
M A SCHROEDER  
J A VANDERHOFF  
M WENSING  
A WHREN  
J M WIDDER  
C WILLIAMSON  
AMSRL-HR-M,  
A W BARROWS

INTENTIONALLY LEFT BLANK.

## USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number ARL-TR-1055 Date of Report April 1996
2. Date Report Received \_\_\_\_\_
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_
4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_
5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_
6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

CURRENT  
ADDRESS

\_\_\_\_\_  
Organization

\_\_\_\_\_  
Name

\_\_\_\_\_  
Street or P.O. Box No.

\_\_\_\_\_  
City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD  
ADDRESS

\_\_\_\_\_  
Organization

\_\_\_\_\_  
Name

\_\_\_\_\_  
Street or P.O. Box No.

\_\_\_\_\_  
City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)  
(DO NOT STAPLE)